MDF THIN

Oil Mud Thinner

General Description

Jet® Thin is a powerful invert oil mud thinner, particularly effective in high weight muds where unacceptably high gel strengths can be generated. The material does not adversely affect other mud properties and in some cases has been shown to improve HTHP fluid loss.

Features / Benefits

• Decreases high mud weights.
• Can be used to decrease gel strength in mud where it is high.
• Does not affect other mud properties

Treatment Rate, Typical

Jet® Thin can be added a rate of 0.5 - 1.5 ppb and is normally sufficient to cure most high rheology problems, however care must be taken not to overdose the system and cause loss of mud rheology. Initial treatment should not be greater than 1.0 ppb.

Add product directly to active mud hopper or mud tanks.

Physical Properties, Typical

Appearance	Mobile liquid
Specific Gravity (77°F)	0.85 @ 20°C
Active Content	80%
Pour Point	23°F
Flash Point	>158°F
Shelf Life (approx.)	730 days

Packaging

Jet® Thin is available in 5 gallon pails, 55 gallon drums and 275 gallon IBC tote tanks from Momentum Drilling Fluids.

Product Data Sheet

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use.

© 2026 Momentum Drilling Fluids. All rights reserved.

Momentum Drilling Fluids
P.O. Box 1366
Houston, TX 77251
1-(844)-Need-Mud
sales@momentumfluids.com