MDF WET PLUS

Wetting agent for OBM

General Description

MDF WET PLUS is an improved wetting agent formulation based off vegetable extract chemistries. It has improved wetting capabilities compared to traditional chemistries and is compatible among commonly used base oils.

Treatment Rate, Typical

Approximately 0.5 to 2 ppb depending on mud weight and temperature. High temperature and high mud weight may require more oil-wetting agent for stability.

Applications

This product is compatible in all commonly used base oils including diesel, linear paraffins, esters, and synthetic olefins.

Physical Properties, Typical

Appearance	Amber liquid
Flashpoint (PMCC)	71 °C (158.9 °F)
Viscosity	120 DR on Fann 35 (100 rpm)
Specific gravity	0.9856
Pour point	<0 °C
Solubility	Soluble in oil

Packaging

MDF WET PLUS is available in 5-gal pails, 55 gallon drums, and 275 gallon IBC totes from Momentum Drilling Fluids

Product Data Sheet

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use.

© 2026 Momentum Drilling Fluids. All rights reserved.

Momentum Drilling Fluids
P.O. Box 1366
Houston, TX 77251
1-(844)-Need-Mud
sales@momentumfluids.com